

# Material Safety Data Sheet **CRYSTAL NAILS ACID FREE PRIMER**

MSDS#: KIP090701-UBP

Page 1 of 1

## Section 1 – Identification of the Substance/Preparation and of the Company/Undertaking

Material / Item Name: ACID FREE PRIMER

MSDS Approval Date 11/27/2002

Chemical Name: Primer

MSDS Prepared by: BSQ

Family: NAIL PRIMER

Manufacturer/Distributor: Litrox Factory Investments LLC (443960-91)

US 8130 SW Portland, Oregon,  
Beaverton-Hillsdale Highway 97225.

Product Use: ADHESION IMPROVEMENT

Product#: 4020001, 4020002, 4020003

## Section 2 - Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#:	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
<u>Ethyl Acetate</u>	141 - 78 - 6	205-500-4	Ethyl Acetate	<u>400 ppm</u>	<u>400 ppm</u>	Not Listed	80-85
2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy)BIS-GMA	1565-94-2	216-367-7	Isopropylidenediphenyl bisoxyhydroxypropyl methacrylate	N/E	N/E	Not Listed	5-10
<u>2-Hydroxy ethyl methacrylate</u>	<u>868-77-9</u>	<u>205-769-8</u>	HEMA	N/E	N/E	Not Listed	5-10

N/E - None Established N/R - Not Reviewed  
N/DA - No Data Available N/A - Not Applicable

Hazard Symbols: Xi, F

Risk Phrases: R11, R36, R43 R66, R67

Safety Phrases: S16, S26, S28A, S33, S36/37

## Section 3 - Hazards Identification

### EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

May cause eye irritation.

**Flammable liquid and vapor!**

May cause skin irritation.

Avoid prolonged or repeated breathing of gases, vapors or mists.

Unstable (reactive) upon depletion of inhibitor. This is only a slight risk.

May be absorbed through the skin.

### Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Inhalation, skin contact, eye contact

Eye Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling.

Skin Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying, cracking, and skin burns.

Ingestion Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.

Inhalation Vapor and mist are irritating to mucous membranes. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

Sub-Chronic Effects May cause headaches, nausea, vomiting and narcotic effect if over-exposed.

Chronic Health Effects (Long-term) No appropriate human or animal health effects data are known to exist.

NOTE: Refer to Section 11, Toxicological Information for Details

### Section 4 - First Aid Measures

First Aid for Eye If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently for 15 min. with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

First Aid for Skin Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek

Revised Date: 11/08/2004 | Replaces Date: 7/12/2004

# Material Safety Data Sheet

MSDS#: KIP090701-UBP

# CRYSTAL NAILS ACID FREE PRIMER

Page 2 of 2

medical attention.

First Aid for Inhalation Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention. First Aid for Ingestion If individual is drowsy or unconscious, do not give anything by mouth; place individual on the leftside with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

## Section 5 - Fire Fighting Measures

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
TAG Closed: 26°F / -3.3°C	400 ppm	750 ° F - 900 ° F
<b>Method:</b>		
Extinguishing Media:	Foam, dry chemical, cold water spray.	
Fire Fighting Instructions:	Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Water spray may be used to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location. Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, carbon dioxide. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back. Prevent buildup of vapors <u>or gases to explosive concentrations.</u>	
Unusual Hazards:		

## Section 6 - Accidental Release Measures

Spill or Release Procedures Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

## Section 7 - Handling and Storage

Handling Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash skin thoroughly after handling.

Storage Store in a well ventilated area. Store @ 70 + 15 ° F, allow some air space above liquid level. Keep containers closed while not in use.

Explosion Hazard Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product ( even just residue) can ignite explosively.

## Section 8 - Exposure Controls / Personal Protective Equipment

Engineering Controls Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

### Personal Protective Equipment

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Revised Date: 11/08/2004| Replaces Date: 7/12/2004

# Material Safety Data Sheet

MSDS#: KIP090701-UBP

## CRYSTAL NAILS ACID FREE PRIMER

Page 3 of 3

Eye/ Face Protection

Skin Protection Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of safety glasses.

Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

### Section 9 - Physical and Chemical Properties

Appearance		Odor & Odor Threshold		pH	Specific Gravity	Viscosity	% Volatile	
Clear liquid		ester like odor		NA	(H2O=1):0.94	15 cps	W/W % : 50+	
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)	
N/DA	N/DA	N/DA	N/DA	(Air=1):1	NA	NA	Insoluble	
<u>Flash Point(°F/°C)</u> TAG Closed: 26°F / -3.3°C			<u>Flammable Limit(vol%)</u> 400 ppm		<u>Auto-ignition Temperature(vol%)</u> 750 ° F - 900 ° F			

### Section 10 - Stability and Reactivity

<b>Stability:</b> Stable	<b>Incompatibility (Materials to Avoid):</b> Avoid oxidizing agents, acids & bases (heat)
<b>Hazardous Decomposition Products:</b> Heated material produces NO2 , CO2 , CO	<b>Hazardous Polymerization:</b> May occur
<b>Conditions to Avoid:</b> Heat, flame, ignition sources.	

### Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
Oral LD50 (rat) : 4.0-6.0g/kg	Dermal LD50 (rabbit): >20mL/kg	Inhalation LC50 (rat) : 3500 - 8000 ppm/4 hours	Rabbit : slight	Rabbit : slight

Since this product contains a mixture of active components, the primary toxicological information is derived from the acetates. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	E.Coli: DNA Damage: 20mol/L	N/DA

### Section 12 - Ecological Information

#### Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

#### Chemical Fate Information

<b>Biodegradability</b>	N/DA
<b>Chemical Oxygen Demand</b>	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

### Section 13 - Disposable Considerations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance

Revised Date: 11/08/2004| Replaces Date: 7/12/2004

# Material Safety Data Sheet **CRYSTAL NAILS ACID FREE PRIMER**

Page 4 of 4

with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

## Section 14 - Transport Information

<b>DOT (49 CFR 172)</b>	
Proper Shipping Name:	Flammable liquids, n.o.s., (ethyl acetate, monomers), 3, UN1993, PGII
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
<b>Emergency Response Guidebook (ERG) #:</b>	<b>128</b>
<b>IATA (DGR):</b>	
Proper Shipping Name:	Flammable liquids, n.o.s., (ethyl acetate, monomers), 3, UN1993, PGII
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	A3
<b>Emergency Response Guidance (ICAO)#:</b>	<b>3L</b>
<b>IMO (IMDG):</b>	
Proper Shipping Name:	Flammable liquids, n.o.s., (ethyl acetate, monomers), 3, UN1993, PGII
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation:	None
<b>Emergency Schedule (EmS)#:</b>	<b>307</b>
<b>Other Information:</b>	<b>Flash point = -3.3°C</b>

## Section 15 - Regulatory Information

### US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutant (HAP), as defined by the U. S. Clean Air Act: <ul style="list-style-type: none"> <li><b>NONE.</b></li> </ul> There are no ODS substances in this product.
Clean Water Act: HS/Priority Pollutant	This product contains the following chemicals listed under the U. S Clean Water Act Hazardous Substance List: <ul style="list-style-type: none"> <li><b>NONE</b></li> </ul> The following chemicals are listed as primary pollutants: <ul style="list-style-type: none"> <li><b>NONE</b></li> </ul>
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and /or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazard are: <ul style="list-style-type: none"> <li>IMMEDIATE (acute) HEALTH HAZARD</li> <li>FIRE HAZARD</li> </ul>
RCRA	This product contains the following chemicals considered to be hazardous waste under RCRA ( 40 CFR 261): <ul style="list-style-type: none"> <li><u>Ethyl Acetate CAS #141 - 78 - 6 RCRA Code: U112.</u></li> </ul>
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List ): <ul style="list-style-type: none"> <li>Ethyl Acetate , CAS #141-78-6, RQ (Lbs) : 5000</li> </ul>
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 ( 40 CFR 370 ). Its hazards are: <ul style="list-style-type: none"> <li>IMMEDIATE (acute) HEALTH HAZARD</li> <li>FIRE HAZARD</li> <li><u>REACTIVE HAZARD</u></li> </ul>
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**Material Safety Data Sheet CRYSTAL NAILS ACID FREE PRIMER**

Page 5 of 5

TSCA Section 8(b): Inventory: TSCASignificant New Use Rule:

This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements. None of the chemicals listed have a SNUR under TSCA.

**State Regulations**

CA Right-to-Know Law: California

No Significant Risk Rule:

MA Right-to-Know Law:

NJ Right-to-Know Law:

PA Right-to-Know Law:

FL Right-to-Know Law:

MN Right-to-Know Law:

Ethyl Acetate CAS #141-78-6

NONE

Ethyl Acetate CAS #141-78-6

Ethyl Acetate CAS #141-78-6

Ethyl Acetate CAS #141-78-6

Ethyl Acetate CAS #141-78-6

Ethyl Acetate CAS #141-78-6

**International Regulations**

CDSL: Canadian Inventory (on Canadian Transitional List)

EINECS: European Inventory:




Ethyl Acetate CAS #141-78-6 is on the DSL List. WHMIS = B2, D2B 2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy)BIS-GMA CAS# 1565-94-2 is n/da for the DSL List. WHMIS = n/da 2-Hydroxyethyl methacrylate CAS #868-77-9 on the DSL List. WHMIS = n/da

**ULTRABOND:**


- Hazard Symbols: **Xi, F**
- Risk Phrases: **R11**, highly flammable, **R36**: Irritating to eyes, **R43**: May cause sensitization by skin contact, **R66**: repeated exposure may cause skin dryness and cracking, **R67**: Vapors may cause drowsiness and dizziness.
- Safety Phrases: **S16**: keep away from sources of ignition- no smoking, **S26**: in case of contact with eyes, rinse immediately, **S28A**: after contact with skin, wash immediately with plenty of water, **S33**: take precautionary measures against static discharges, **S36/37**: Wear suitable protective clothing and gloves.

**Section 16 - Other Information****Hazard Rating System (Pictograms)**

NFPA:



HMIS:



Revised Sections since Last Version:

| Updating formatting and Section II % content revision

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

Revised Date: 11/08/2004| Replaces Date: 7/12/2004