

Material Safety Data Sheet

CRYSTAL NAILS LIQUID

Section 1 – Identification of the Substance/Preparation and of the Company/Undertakin

Material/Product Name: Liquid

Chemical Name: N/A

Family: Monomer

Product Use: Nail Liquid

Product #: 1000203-5

MSDS Approval Date:

1/10/2001

MSDS Prepared by:

BSQ

Manufacturer/Distributor: Litrox Factory Investments LLC (443960-91)

US 8130 SW Portland, Oregon,

Beaverton-Hillsdale Highway 97225.

Section 2 - Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL		
Ethyl Methacrylate	97-63-2	202-597-5	Ethyl methacrylate	N/E	N/E	Not Listed	75-80
Hydroxy propyl methacrylate	27813-02-1	248-666-3	Hydroxypropyl Methacrylate	N/E	N/E	Not Listed	10-15
Tetraethylene glycol dimethacrylate	109-17-1	203-653-1	PEG-4 Dimethacrylate	N/E	N/E	Not Listed	5-10
N,N-Dimethyl-p-toluidine	99-97-8	202-805-4	Dimethyltolylamine	N/E	N/E	Not Listed	0-1
D&C Violet #2	81-48-1	201-353-5	CI 60725	N/E	N/E	Not Listed	0-1
FD&C Blue #1	3844-45-9	223-339-8	CI 42090	N/E	N/E	Not Listed	0-1
N/E - None Established N/R - Not Reviewed	N/DA - No Data Available N/A - Not Applicable						

Hazard Symbols: Xi F

Risk Phrases: R11, R36/ 37/38, R43

Safety Phrases: S9, S16, S29, S33, S36/37/39, S45

Section 3 - Hazards Identification**EMERGENCY OVERVIEW**

This information is based on findings from related or similar materials.

- **Flammable liquid and vapor!**
- May cause eye irritation.
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors or mists.
- Please read entire MSDS for additional information.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry	Inhalation , skin , eyes
Eye	Vapor concentrations may cause irritation of eyes. Liquid contact with eyes can cause irritation and possible corneal damage.
Skin	Liquid concentration may cause moderate skin irritation. Repeated or prolonged contact may cause allergic skin rashes, itching and swelling which becomes evident on re-exposure to this product.
Ingestion	Causes irritation, a burning sensation of the mouth, throat and respiratory tract and abdominal pain.
Inhalation	High vapor concentrations may irritate the respiratory system. Prolonged exposure can lead to headaches , nausea , drowsiness and unconsciousness.
Sub-Chronic Effects	Unlikely to present a cancer hazard in man.

NOTE: Refer to Section 11, Toxicological Information for Details

Section 4 - First Aid Measures

First Aid for Eye	Flush with water for 15 minutes, including under eyelids. Seek medical help if discomfort persists.
First Aid for Skin	Wash thoroughly with soap and water. Remove contaminated clothing and wash before reuse. Seek medical attention if discomfort persists.
First Aid for Inhalation	Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give artificial respiration. Get medical help if discomfort persists.
First Aid for Ingestion	Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.

Revised Date: 8/22/2006 | Replaces Date: 10/27/2004

Section 5 - Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
Tag Closed Cup: 68°F/20°C	LEL : 2% ; UEL : 2.5%	392.8 ° C

Method:

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical or Carbon Tetrachloride.

Fire Fighting Instructions: Wear self-contained breathing apparatus and full protective gear. Water may be ineffective unless used as a fine spray or fog. Use water spray to cool the exposed containers of methacrylate monomer.

Unusual Hazards: Vapors may travel to source of ignition and flash back. Avoid ignition sources or excessive temperatures. Heat can induce polymerization with rapid release of energy. Closed containers may rupture explosively. Spontaneous polymerization may occur with prolonged aging.

Section 6 - Accidental Release Measures

Spill or Release Procedures Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Section 7 - Handling and Storage

Handling Keep away from heat, sparks, flames and other sources of ignition. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use with adequate ventilation. Ground all metal containers when transferring and use explosion-proof equipment. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.

Storage Store in a cool, dry area. Keep container closed when not in use. Store at ambient temperatures out of direct sunlight. Store in a well ventilated place. Store in accordance with National Fire Protection Association recommendations. Maintain air space inside storage containers. Inhibitor requires air (oxygen) contact to function. Check inhibitor levels after 3 months and return to original level.

Explosion Hazard Avoid ignition sources or excessive temperatures. Heat can induce polymerization with rapid release of energy. Closed containers may rupture explosively. Spontaneous polymerization may occur with prolonged aging.

Section 8 - Exposure Controls / Personal Protective Equipment

Engineering Controls Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying material.

Material Safety Data Sheet CRYSTAL NAILS LIQUID

Skin	Protection Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Neoprene and Nitrile rubber is better than PVC.
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Section 9 - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity		% Volatile	
Blue-violet liquid	sharp ester-like odor	N/A	(H20=1): 0.918	<1mPas @ 20°C		W/W %: 99+	
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporatio n Rate	Ignition	Solubility In Water (20°C)
243°F/117°C N/DA	N/A	1.25	mm Hg: 0.69 kPa @ 38°C	(Air =1) : 3.9	ButylAcetate =1: 1.5	N/A	0.5g/100g @20°C

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
Tag Closed Cup: 68°F/20°C	LEL : 2% ; UEL : 2.5%	392.8 ° C

Section 10 - Stability and Reactivity

Stability: Stable Hazardous Decomposition Products: Oxides of carbon when burned. Conditions to Avoid: Temperatures above 60 F, oxidizing or reducing agents, peroxides and amines, storage in absence of inhibitor, and inadvertent addition of catalyst.	Incompatibility (Materials to Avoid): Reducing and oxidizing agents and UV light. Hazardous Polymerization: May occur
--	--

Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
Oral (Rat) LD50 : 13300mg/kg	Dermal(Rabbit) LD50 : > 9100 mg/kg	Inhalation (Rabbit) LD 50: 3800 ppm	N/DA	N/DA

Since this product contains a very low concentration of active components, the primary toxicological information is from the monomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/DA	Test positive as a mutagen on laboratory animals	N/DA

Section 12 - Ecological Information**Ecotoxicological Information**

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13 - Disposable Considerations

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state

and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14 - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Flammable liquids, n.o.s., (ethyl methacrylate, hydroxy propyl methacrylate), 3, UN1993, PGII
Identification Number:	UN1993
Marine Pollutant:	No
Special Provisions:	T8, T31
Emergency Response Guidebook (ERG) #:	128
IATA (DGR):	
Proper Shipping Name:	Flammable liquids, n.o.s., (ethyl methacrylate, hydroxy propyl methacrylate), 3, UN1993, PGII
Class or Division:	3
UN or ID Number:	UN1993
Packaging Instructions:	
Emergency Response Guidance (ICAO)#:	
IMO (IMDG):	
Proper Shipping Name:	Flammable liquids, n.o.s., (ethyl methacrylate, hydroxy propyl methacrylate), 3, UN1993, PGII
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation:	None
Emergency Schedule (EmS)#:	
Other Information:	Flash point = 20°C

Section 15 - Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP's) as defined by the U. S. Clean Air Act: <ul style="list-style-type: none"> NONE This product does not contain any Class1 or Class 2 ODS.
Clean Water Act:	This product contains the following Hazardous Substances as defined by the CWA: <ul style="list-style-type: none"> NONE This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> Immediate (acute) health hazard Fire hazard.
RCRA	This product is considered to be a hazardous waste under RCRA (40 CFR 261) RCRA Code: <ul style="list-style-type: none"> Ethyl methacrylate, CAS# 97-63-2, RCRA Code: U118 Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List). <ul style="list-style-type: none"> Ethyl Methacrylate, CAS# 97-63-2, RQ (Lbs): 1000
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> Immediate (acute) health hazard Fire hazard
SARA Title III: Section 313:	This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> NONE

Material Safety Data Sheet

MSDS#: KIM011001-R1L

CRYSTAL NAILS LIQUID


Page 5 of 5

TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements. None of the chemicals in this material have a SNUR under TSCA.
-------------------------------	--

State Regulations

CA Right-to-Know Law: California No Significant Risk Rule:	NONE NONE
MA Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
NJ Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
PA Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
FL Right-to-Know Law:	Ethyl Methacrylate CAS #97-63-2
MN Right-to-Know Law:	NONE

International Regulations



y (on Canadian Transitional List)	
EINECS: European Inventory:	

Ethyl Methacrylate DSL regulatory status: Included, WHMIS: B2: flammable liquid D-2B: Toxic
 N,N-dimethyl-p-toluidine DSL regulatory status: Included, WHMIS: n/da Hydroxypropyl methacrylate DSL regulatory status: Included, WHMIS: D2B Tetraethylene glycol dimethacrylate, DSL regulatory status: Included, WHMIS: n/da

- HAZARD SYMBOLS: **Xi, F: Irritant, Highly Flammable**
- RISK PHRASES: **R11: highly flammable, R36/37/38: Irritating to eyes, respiratory system and skin, R43: May cause sensitization by skin contact**
- SAFETY PHRASES: **S9: keep container in a well ventilated place, S16: keep away from sources of ignition- no smoking, S29: do not empty into drains, S33: take precautionary measures against static discharges, S36/37/39: wear suitable protective clothing, gloves and eye/face protection, S45: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)**

Section 16 - Other Information

Hazard Rating System (Pictograms)

NFPA:		HMIS:	
-------	---	-------	---

Revised Sections since Last Version:

- 10/12/2004 Overall Format Update.
- 10/27/2004 Overall Format Update.
- 08/22/2006 Section 2. FD&C Blue #1 added at 0-1%.

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.