

Material Safety Data Sheet

XTREME CLEAR GEL

Section 1 – Identification

Product Name: XTREME CLEAR GEL

Chemical Name: N/A

Family: UV GELS

Product Use: NAIL GEL

Product #: 4020141

Manufacturer/Distributor: Litrox Factory Investments LLC (443960-91)
 US 8130 SW Portland, Oregon,
 Beaverton-Hillsdale Highway 97225.

Section 2 - Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- May be slightly toxic.
- May cause moderate skin injury (reddening & swelling).
- May cause eye irritation.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

Eye No specific information available. Contains materials that are essentially nonirritating, but contact may cause slight transient irritation.

Skin No specific information available. Contains materials that may cause moderate skin injury (reddening and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that are considered to be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be irritating.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

Section 3 - Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL		
Polyurethane Acrylate Oligomer	Exempt	N/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E	N/E	Not Listed	80-90
Isobornyl Methacrylate	7534-94-3	231-403-1	Isobornyl Methacrylate	N/E	N/E	Not Listed	5-15
Hydroxycyclohexyl phenyl ketone	947-19-3	213-426-9	Hydroxycyclohexyl phenyl ketone	N/E	N/E	Not Listed	0-2
D&C Violet #2	81-48-1	201-353-5	CI60725	N/E	N/E	Not Listed	0-0.5
N/E - None Established N/R - Not Reviewed	N/DA - No Data Available N/A - Not Applicable	* See section 16					

Polyurethane Acrylate Oligomer: Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S14, S37, S62

Isobornyl Methacrylate: Hazard Symbol – Xi Risk Phrases – R36/37/38 Safety Phrases – S26, S27, S28, S29, S30, S33, S35, S36

Hydroxycyclohexyl Phenyl Ketone: Hazard Symbol: Xi Risk Phrases: R36, R37, R38 Safety Phrases: S26, S37

See Section 16 for Risk and Safety Phrase Key

Section 4 - First Aid Measures

First Aid for Eye Flush eyes with water for 15 minutes, including under eyelids. If irritation continues, seek medical attention.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion If appreciable quantities are swallowed, seek medical attention.

Material Safety Data Sheet

XTREME CLEAR GEL

Section 5 - Fire Fighting Measures

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
>212 °F/100 °C Setaflash	No Data	No Data

Method:

Extinguishing Media:	Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.
Fire Fighting Instructions:	Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists.
Unusual Hazards:	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a stream of water to control fires since frothing can occur.

Section 6 - Accidental Release Measures

Spill or Release Procedures -	Spontaneous polymerization can occur. Although material is non-flammable please try to eliminate all ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detergent and water solution; rinse with water, but minimize water use during clean-up. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.
-------------------------------	--

Section 7 - Handling and Storage

Handling	Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential. When handling gel for product use, do not heat above 100°F/38°C or disassociation of resins in product may occur. Material is UV light sensitive, avoid prolonged exposure to light/heat.
Storage	Store in a cool place, away from heat and light. Store at temperatures below 100°F/38°C.
Explosion Hazard	High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in explosions and the violent rupture of storage vessels or containers.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls	Local exhaust recommended to control exposure which may result from operations generating aerosols and hot operations generating vapors.
----------------------	--

PERSONAL PROTECTIVE EQUIPMENT

General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/ Face Protection	Chemical splash goggles.
Skin Protection	Impervious gloves (Neoprene).
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Material Safety Data Sheet XTREME CLEAR GEL

Section 9 - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	% Volatile		
Clear, viscous liquid	characteristic acrylate odor	NA	(H ₂ O=1) : 1.15	N/DA	By Volume: < 0.5		
Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C:< 0.01	No Data	No Data	No Data	Insoluble
Flash Point(°F/°C)		Flammable Limit(vol%)		Auto-ignition Temperature(vol%)			
>212 °F/100 °C Setaflash		No Data		No Data			

Section 10 - Stability and Reactivity

Stability

Normally Stable

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

Conditions to Avoid:

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.

Hazardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No information available	No information available	No information available	No information available	No information available
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.				
Sensitization		Mutagenicity		Sub-chronic Toxicity
No information available		No information available		No information available

Section 12 - Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA

Chemical Fate Information

Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13 - Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the generators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Section 14 - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	None
Emergency Response Guidebook (ERG) #:	N/A
IATA (DGR):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	None
Emergency Response Guidance (ICAO)#:	N/A
IMO (IMDG):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Special Provisions & Stowage/Segregation:	None
Emergency Schedule (EmS)#:	N/A
Other Information:	Flash point >100°C

Section 15 - Regulatory Information**US Federal Regulations**

Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act: <ul style="list-style-type: none"> • NONE This product contains no ODS's
Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant List.
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.
TSCA Section 8(b): Inventory: TSCA Significant New Use Rule:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements. None of the chemicals listed have a SNUR under TSCA.

Material Safety Data Sheet XTREME CLEAR GEL


State Regulations

CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	NONE
NJ Right-to-Know Law:	NONE
PA Right-to-Know Law:	NONE
FL Right-to-Know Law:	NONE
MN Right-to-Know Law:	NONE

International Regulations

CDSL: Canadian Inventory (on Canadian Transitional List)	Hydroxycyclohexyl phenyl ketone CAS # 947-19-3 is on the DSL list. WHMIS = n/da Isobornyl Methacrylate CAS # 7534-94-3 is on the DSL list. WHMIS = n/da
---	--

Labeling according to EC directives – 1999/45/EC

European Community: 	Xtreme Clear Gel MPH-1178A: <ul style="list-style-type: none"> HAZARD SYMBOLS: Xi: Irritant Risk Phrases: R20: Harmful by inhalation, R43: May cause sensitization by skin contact. Safety Phrases: S24/25: Avoid contact with skin and eyes, S28A: After contact with skin, wash immediately with plenty of water, S37: Wear suitable protective gloves, S45: In case of accident, or if you feel unwell, seek medical advise immediately (show the label where possible)
--	---

Section 16 – Other Information

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol:

Xi – Irritants

Risk Phrases:


R36/37/38 Irritating to eyes, respiratory system and skin

Safety Phrases:


S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way; S36 Wear suitable protective clothing; S37 Wear suitable gloves; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label

Hazard Rating System (Pictograms)

NFPA:



HMIS:



Material Safety Data Sheet

XTREME CLEAR GEL

MSDS Prepared by:	JRR
Revision History:	02/08/2008 Initial issue
	04/30/2008 Updated INCI name for Polyurethane Acrylate Oligomer. * Most Keystone gels are composed of oligomers made primarily from urethane methacrylates. Keystone is using the designation Di HEMA Trimethylhexyl Dicarbamate, the official INCI name of urethane dimethacrylate, which is substantially the equivalent of Polyurethane Acrylate Oligomer.
	09/17/2008 Updated section 16
	10/22/2008 Updated format
	11/14/2008 Updated Risk and Safety Phrases
	03/18/2009 Updated to meet Globally Harmonized System requirements. Added the EU address to section 1. Switched location of section 2 with section 3. Changed the title in sections 1, 8, and 13. Moved MSDS preparation to section 16.
	07/16/2009 Added MPH-1178A designation.

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

KRP components are provided on an as is basis without warranties of any kind either expressed or implied. KRP does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said KRP components.